



## POLYMAX INSULATION

Other Names: **Prime, Easy Baffle, Absorb, Thermal Batts, Acoustic/Thermal Batts, Building Blanket, MSB, HVAC, Thermaflex, MAB** and **Filter Media**

### Uses

Acoustic and Thermal Insulation used in buildings, Industrial applications, HVAC systems, OEM and Automotive.

### Manufacturer

Martini Industries Pty Ltd  
4 MacDonald Road  
Ingleburn NSW 2565  
Australia

Ph 02 9829 2299  
Fax 02 9829 2211  
Web [www.polymaxinsulation.com.au](http://www.polymaxinsulation.com.au)  
Email: [admin@martini.net.au](mailto:admin@martini.net.au)

### Hazards

Classified as Non-Hazardous according to the criteria of the Australian Safety and Compensation Council ASCC. Approved criteria for classifying Hazardous substances. [NOHSC: 1008] 3rd edition.

### Composition

Organic Long Chain Synthetic Polymer.

### First Aid

Swallowed / Eye / Skin / Inhaled: No special precautions.

### Fire Fighting Measures

Limited flammability properties when tested to AS1530.3 (see below). However, the fibres will melt if exposed to temperatures above 250°C. Plastic packaging and facings used may decompose or burn at or below this temperature. If subject to fire, evacuate area and contact emergency services. Use water fog to cool affected product and packs.

### Storage and Transport

No Special Requirements.

### Disposal

Product is recyclable. If necessary product can be disposed of in an approved landfill.

### Fire/Explosion Hazard

Relatively low flame response. Will not explode. Use any fire fighting appliance. Like most organic materials gives off CO, CO<sub>2</sub> and H<sub>2</sub>O during combustion.

### Personal Protection

No Precautions necessary.

### Ecological Information

Product does not contain any ozone-depleting chemicals.  
100% Recyclable.

[www.polymaxinsulation.com.au](http://www.polymaxinsulation.com.au)





## POLYMAX INSULATION

### Physical Properties and Description

<b>Appearance:</b>	White, Black or Grey polyester waddings, may include laminated facing materials such as foils or fabrics									
<b>Odour:</b>	None									
<b>Alkalinity:</b>	pH: 7.8 (pH 7 is neutral)									
<b>Boiling Point:</b>	N/A									
<b>Melting Point:</b>	250°C									
<b>Vapour Pressure:</b>	N/A									
<b>Specific Gravity:</b>	1.38									
<b>Solubility:</b>	N/A									
<b>Percentage Volatiles:</b>	None									
<b>Flash Point:</b>	N/A									
<b>Decomposition Temp:</b>	> 250°C									
<b>Lower/Upper Exposure Limits:</b>	N/A									
<b>Moisture Absorption:</b>	Exposure to an atmosphere of 50°C and 95% RH for four days gives a moisture absorption of less than 0.2% by volume.									
<b>Fire Resistance</b>	When tested in accordance with AS1530.3 (1999), "Early Fire Hazard Properties of Materials", exhibits the following characteristics:	<table border="1"> <tr> <td>Ignitability</td> <td>0</td> </tr> <tr> <td>Spread of Flame</td> <td>0</td> </tr> <tr> <td>Heat Evolved</td> <td>0</td> </tr> <tr> <td>Smoke Developed</td> <td>0-1</td> </tr> </table>	Ignitability	0	Spread of Flame	0	Heat Evolved	0	Smoke Developed	0-1
Ignitability	0									
Spread of Flame	0									
Heat Evolved	0									
Smoke Developed	0-1									

This MSDS is issued by Martini Industries Pty Ltd in accordance with Worksafe Australia Guidelines. The information must not be altered, added to or deleted. Martini Industries will publish a new MSDS if any a change occurs in the product specifications, information about the product, or Worksafe Australia guidelines. Martini Industries will not accept responsibility for any loss or damage caused by unauthorised changes to the content of the MSDS made by any other person or organisation.

This information is provided in good faith and to the best of Martini Industries' knowledge, was accurate at the time of publication. No responsibility can be accepted for any errors or omissions. Users should decide for themselves as to the suitability of this information for their particular purposes or specific circumstances. Since information contained in this document may be applied under conditions beyond Martini Industries' control, no responsibility can be accepted by Martini Industries for any loss or damage caused by any person acting or refraining from actions as a result of this information.

Disclaimer: The information in this brochure is believed to be true at the time of publication. Martini Industries Pty Ltd reserves the right to change specifications without notice, and have no obligation or liability for persons misrepresenting or misusing this information in any manner whatsoever.

[www.polymaxinsulation.com.au](http://www.polymaxinsulation.com.au)

